Solid State Cell Assembled

FEATURES

Compatible
Same Utility Condition with Li-ion

Safer
No leakage. No fire
No reaction to solid-solid contacts

Stable
Good cycle performance
AT room and high temperature

Solidified
Electrolyte injected can be Solidified inside the cell or electrode

Client Test

Cathode	High-Ni/NCM HV LCO
Anode	Li / Si
Capacity	10Ah
E.D.(Wh/kg)	300

Nail Test	passed
Crush Test	passed
8V Overcharge	passed



• DRONE BATTERY

- V : 44.4 (33.6 ~ 50.4)
- Weight (Kg) : 4.7
- Size : 213 x 128 x 91
- Discharge : 5C Conti
- Charge : 1C Conti

- V : 48.1 (36.4~ 56.4)
- Weight (Kg) : 5.6
- Size : 213 x 150 x 91
- Discharge : 5C Conti
- Charge : 1C Conti

- V : 25.9 (19.6 ~ 29.4)
- Weight (Kg) : 2.3
- Size : 195 x 77 x 77
- Discharge : 5C Conti
- Charge : 1C Conti

- V : 22.2 (16.8 ~ 25.2)
- Weight (Kg) : 1.98
- Size : 195 x 77 x 67
- Discharge : 5C Conti
- Charge : 1C Conti

- V : 22.2 (16.8~ 25.2)
- Weight (Kg) : 1.55
- Size : 195 x 77 x 52
- Discharge : 5C Conti
- Charge : 1C Conti

- V : 22.2 (16.8~ 25.2)
- Weight (Kg) : 2.65
- Size : 213 x 91 x 70
- Discharge : 5C Conti
- Charge : 1C Conti

- V : 22.2 (16.8~ 25.2)
- Weight (Kg) : 2.38
- Size : 213 x 91 x 65
- Discharge : 5C Conti
- Charge : 1C Conti

VISION

Energy storage in solid state, Guard the blue sky

MISSION

Achieve safe, efficient, low cost, long-life energy storage

VALUES

Innovation-driven, customer-oriented;

Quality assured, Knowledge and practice united.

- Contact : Cool Choi
- Email : coolchoi@cooleletric.com
- URL : www.kurudenki.co.kr
- Tel : 010-8891-4173
- Company : Kuru Denki Co., Ltd